

THE GLOBAL SPECIALIST FOR PVC COMPOUNDS

DATA SHEET

norvinyl® GA.54.10.00798

Description	Flexible PVC Extrusion Compound
Colour	Natural
Application	Profiles
Compliances	REACH Regulations 1907/2006 and 2011/10/EC (RoHS)
Form	Pellets
SDS No.	

TYPICAL PROPERTIES

	Test Method	Units	Value
General Properties			
Density (varies with colour)	EN ISO 1183-1A	g/cm ³	1,187 ±0,01
Hardness (15 sec@23°C)	EN ISO/R 868	Shore A	54 ±2
Other Properties			
Cold Flex	EN ISO 458	°C	-25
Thermal Stability	EN ISO 182-1	Min	60

*Material tested on extruded profile. Actual performance may vary depending upon product design. Customers are advised to verify product as required.

Issue 30 October 2018

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given, nor is to be implied with respect of such information. Users should make their own enquiries to determine the suitability of products for any particular application. Freedom from patents, copyright and registered designs cannot be determined.

INEOS Compounds Aycliffe Limited

School Aycliffe Lane
Newton Aycliffe
Co. Durham DL5 6EA
United Kingdom

Tel: +44 (0) 1325 300555
Fax: +44 (0) 1325 303001

INEOS Compounds Sins, Switzerland

INEOS Compounds Switzerland AG
Industrie Nord 2
CH-5643 Sins
Switzerland

Tel: +41 41 78 98 200
Fax: +44 41 78 98 234

INEOS Compounds Helsingborg, Sweden

INEOS Compounds Sweden AB
Gevärsgatan 4
SE-254 66 Helsingborg
Sweden

Tel: +46 42 250 200
Fax: +46 42 250 280

INEOS
Compounds

www.ineos.com