



## Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Glas - PMMA, frostat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	5,48kg / 6,5kg
Förpackning mått [cm]	15x15x91
LED	Cree DK210704 V2 JB2835 3V 3K (Produktblad)
Drivdon	TCI MICRO MD 10W 350mA 127040 Triac (Produktblad)
Led modul effekt	7,4W
Armaturljus effekt	9,2W
Lumen modul	1370lm
Lumen ut	897lm
Led modul effekt	185,1lm/W
Armaturens effekt	97,5lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>72 000h
Energieffektivitetsindex (EEI)	A <sub>+</sub> / EPREL
Effektfaktor	PF 0,9
THD-faktor	10%
Ta nominell:	+25°C
Inrush current	2A / 50µs

## Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer, BIM Revit, BIM ArchiCAD

